


TRUCK MIXER LT 10.7H



α	10 °
Ht	2793 mm
Hs	1774 mm
Lt	6901 mm
La	5363 mm
Lp	1184 mm

Data sheet

Nominal capacity	10(11) m ³
Geometrical volume	17,648 m ³
Capacity in water	10,241 m ³
Drum speed	0-14 rev/min
Filling capacity	10 ^m /m ³
Unloading capacity	10 ^m - 40 ^m /m ³ depending on concrete slump
Weight (empty)	4.400 kg
Vehicle	8x4
Rollers	n. 2 diam. 280 mm

Drum walls made in 30MnB5 anti-wear resistant steel - HB 200/220 N/mm² (4mm thickness)
 Mixing blades made in 30MnB5 anti-wear resistant steel - HB 200/220 N/mm² (4mm thickness)

Motion

H version: by P.T.O. on truck engine (excluded from our supply)

TRUCK MIXER LT 10.7H



Controls

By cable with control box

Hydrostatic transmission

Eaton 64.21 (105 cm³/rev) variable displacement hydraulic pump with 25 cm³/rev feeding pump

Eaton 54.31 (90 cm³/rev) fixed displacement hydraulic motor

OK 2.7 (70.000 Nm) double stage planetary gearbox

Oil cooler (42.000 BTU) built in oil tank, complete with cartridge filter with indicator and electric fan with thermostat

Water system

650l steel water tank with level indicator

LTC30 water pump (450 l/min at 4 bar) belt driven

0-500l water meter

Standard features

- 180° swivelling discharging chute with support and mechanical jack for lifting
- 2 Polystone lightweight extension chutes with holders
- Anti-wear resistant plate on discharging hopper
- Double inspection manhole
- Inspection ladder
- Wash off hose on ladder pedestal
- Drum lock (for safety maintenance operations)
- Carrying rollers made in C45 special steel
- Steel surfaces shotblasted in SA 2,5 grade
- Double primed in antirust painting



Optionals / Variations

- Additional extension steel chute L=1000 mm
- Additional short extension steel chute L=500 mm
- Additional polystone extension chute (light construction) L=1000 mm
- Additional short polystone extension chute (light construction) L=500 mm
- Telescopic discharging chute LT 555 with funnel
- Funnel chute ø195 mm
- Hinged extension steel chute
- Hinged extension Polystone chute (light construction)
- Flap on discharging chute
- Anti wear protection sheet on feeding hopper
- Anti wear protection sheet on discharging chute
- Vibrator on discharging chute
- Half hydraulic drum cover
- Full hydraulic drum cover
- Hydraulic manometer with large gauge ø 65 mm placed at the rear
- Hydraulic manometer with large gauge ø 100 mm placed at the rear
- Water connection on two sides
- Additional valve for water tank closing

TRUCK MIXER LT 10.7H



- Rear steel mud-guards and supports (one pair)
- Rear aluminium mud-guards and supports (one pair)
- Rear aluminium mud-guards with the smooth surface on the outside and supports (one pair)
- Mud-guards for front axle and supports (one pair)