


TRUCK MIXER LT 8XL.7D



| | |
|----------|---------|
| α | 14 ° |
| Ht | 2735 mm |
| Hs | 1656 mm |
| Lt | 6739 mm |
| La | 4502 mm |
| Lp | 1184 mm |

Data sheet

| | |
|--------------------|--|
| Nominal capacity | 8,5(9,5) m ³ |
| Geometrical volume | 14,014 m ³ |
| Capacity in water | 9,580 m ³ |
| Drum speed | 0-14 rev/min |
| Filling capacity | 15"/m ³ |
| Unloading capacity | 15" - 40"/m ³ depending on concrete slump |
| Weight (empty) | 4.150 kg |
| Vehicle | 8x4 |
| Rollers | n. 2 diam. 280 mm |

Drum walls made in 30MnB5 anti-wear resistant steel - HB 200/220 N/mm² (4 mm thickness)
 Mixing blades made in 30MnB5 anti-wear resistant steel - HB 200/220 N/mm² (4 mm thickness)

Motion

D version: by Deutz F5L912 auxiliary engine, 5 cylinders, air cooled

TRUCK MIXER LT 8XL.7D



Controls

By cable with control box

Hydrostatic transmission

Eaton 46.21 (73.5 cm³/rev) variable displacement hydraulic pump with 25 cm³/rev feeding pump
Eaton 46.31 (73.5 cm³/rev) fixed displacement hydraulic motor
OK 2.6 (60.000 Nm) double stage planetary gearbox
Oil cooler (42.000 BTU) built in oil tank, complete with cartridge filter with indicator and electric fan with thermostat tropical type
For D version: control panel with led and acoustic alarm of oil overheating, electric fan and thermostat functioning. Working hour meter

Water system

650l steel water tank with indicator. (option:1000l)
LTC30 water pump (450 l/min at 4 bar) belt driven
0-500l water meter

Standard features

- 180° swivelling discharging chute with support and mechanical jack for lifting
- 2 Polystone lightweight extension chutes with holders
- Anti-wear resistant plate on discharging hopper
- Inspection manhole
- Inspection ladder
- Wash off hose on ladder pedestal
- Drum lock (for safety maintenance operations)
- Mixer frame "C" shaped
- Carrying rollers made in C45 special steel
- Steel surfaces shot blasted in SA 2,5 grade
- Double primed in antirust painting



Optionals / Variations

- Additional extension steel chute L=1000 mm
- Additional short extension steel chute L=500 mm
- Additional polystone extension chute (light construction) L=1000 mm
- Additional short polystone extension chute (light construction) L=500 mm
- Telescopic discharging chute LT 555 with funnel
- Funnel chute ø195 mm
- Hinged extension steel chute
- Hinged extension Polystone chute (light construction)
- Flap on discharging chute
- Anti wear protection sheet on feeding hopper
- Anti wear protection sheet on discharging chute
- Vibrator on discharging chute
- Half hydraulic drum cover
- Full hydraulic drum cover
- Hydraulic manometer with large gauge ø 65 mm placed at the rear
- Hydraulic manometer with large gauge ø 100 mm placed at the rear

TRUCK MIXER LT 8XL.7D



- Water connection on two sides
- Additional valve for water tank closing
- Rear steel mud-guards and supports (one pair)
- Rear aluminium mud-guards and supports (one pair)
- Rear aluminium mud-guards with the smooth surface on the outside and supports (one pair)
- Mud-guards for front axle and supports (one pair)